

PRODUCT INFORMATION

<i>DESCRIPTION</i>	Dulux Professional Interior A300 Matt is a low odour, durable emulsion with a smooth matt finish. It is certified to Singapore Green Building Products Labelling Scheme.
<i>USAGE</i>	Suitable for all normal interior masonry surfaces including brickwork, plaster, cement, concrete as well as hard and soft wallboards.
<i>PACK SIZE</i>	20 litres
<i>COLOUR RANGE</i>	Refer to Colour Collaterals
<i>PRODUCT CODE</i>	A901

PHYSICAL FILM PROPERTIES

<i>Water Resistance</i>	Resistant to the levels of atmospheric humidity present in normal interior environments. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.
-------------------------	--

PRODUCT DATA

<i>Composition</i>	Pigment : Lightfast Non-Lead Pigments Binder : Acrylic Emulsion Solvent : Water
<i>Volume Solid</i>	White 30% (nominal), other colours will vary
<i>Drying Time</i>	Single coat at standard thickness:
<i> Touch Dry</i>	Dependent on temperature and humidity
<i> Recoat</i>	2 - 4 hours
<i>Theoretical Film Thickness</i>	Dry: 30 - 40 microns
<i>Theoretical Coverage</i>	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 9 - 10 m ² /litre.
<i>Finishing</i>	Matt

CERTIFICATE



APPLICATION GUIDE

Surface Preparation

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. Remove all loose and defective paint or powdery residues by thorough brushing and scraping, using a stiff fiber brush. Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Treat any areas affected by mould, lichens, algae and moss with Dulux Professional Fungicidal Wash. Repair any surface defects with an appropriate filler. Surfaces that remain powdery, friable or chalky after thorough preparation should be sealed with one coat of an appropriate Sealer (see below System Recommendation). Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust. Do not paint if the wall is saturated with dampness. (Protimeter reading higher than 16%). Allow excess moisture to evaporate.

Application Tools

By roller, brush or conventional/airless spray.

Dilution

Ready to use.

Note: Excessive dilution from that recommended will result in low coverage and may impact application properties and colour.

System Recommendation

Substrate	Sealer (1 coat)	Topcoat (2 coats)
New wall surface	Dulux Professional Interior Sealer A500	Dulux Professional Interior A300 Matt
Old wall surface	Dulux Professional Diamond Solventbased Sealer A1000	

For alternative coating systems, please refer to our Sales Representative

Cleaning Up

Clean all equipment with clean water immediately after use.

HEALTH, SAFETY & ENVIRONMENT INFORMATION

Please refer to Product Safety Data Sheet